

MR (non-magnetic) Fire Extinguisher

Part number 21005726

Multipurpose use

Disposable

UL Rated 3-A, 40-B:C



Description

The 5 lb. Kidde Dry Chemical Fire Extinguisher is manufactured using special components. It has been independently tested and has received the MR Conditional Rating. Suitable for use on the following types of fire:

- Class A (trash, wood & paper)
- Class B (liquids)
- Class C fires (energized electrical equipment)

XL5 MR



MR CONDITIONAL

This extinguisher has been tested in a 3 Tesla MR imaging system and found to pose no magnetic safety hazards.

At a Glance

- Model XL5 MR
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A:40-B:C
- Tested MR Conditional
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Product Specification

Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.75 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	Included

Features

- Safe to use around MRI rooms
- Recommended for use outside MRI rooms
- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Easy-to-pull safety pin
- Impact resistant nylon handle & valve assembly
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Approved wall hanger & screws
- Clean white powder coated cylinder for corrosion protection

MR Extinguisher Markings Conform to New FDA Recommendations Contained in ASTM-2503-05 "Standard for Marking Medical Devices and Other Items for Safety in Magnetic Resonance Environments".

Packaging Options



SINGLE PACK

