

Regular Dry Chemical Fire Extinguishers



Features

- Agency Listings/Approvals:
 - UL Listed
 - ULC Listed
 - USCG Approved with approved bracket
- Available in four sizes: 2 $\frac{3}{4}$, 5 $\frac{1}{2}$, 10 and 20 lb.
- Temperature Range: -40°F to 120°F (-40°C to 49°C)
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- Corrosion-resistant aluminum valve and handle
- Universal pictorial labels with operator instructions
- Twelve year interval between hydrotests
- Six year warranty

UL Listed Models

- K275RB
- K5R
- K10R
- K20R

ULC Listed Models

- K275RB-C
- K5R-C
- K10R-C
- K20R-C

**UL and ULC Listed Models
Six Year Warranty**



Great Value: Exceptional Performance—The Kidde Fire Systems Regular Dry Chemical Fire Extinguishers are designed for occupancies that do not require Class A ratings, or as a supplement to normal occupancy fire extinguishers.

Rated for use on flammable or combustible liquid fires, the Kidde Fire Systems line of Regular Dry Chemical Extinguishers provide cost-effective fire protection solutions for manufacturing processes involving dip tanks, spray paint operations, flammable storage areas, paint storage areas and all Class B fire hazards.

Specifications

		K275RB	K275RB-C	K5R	K5R-C	K10R	K10R-C	K20R	K20R-C
Nominal Capacity	lb.	2.75	2.75	5.50	5.50	10.00	10.00	20.00	20.00
	kg	1.25	1.25	2.49	2.49	4.54	4.54	9.07	9.07
UL Fire Rating		10B:C	10B:C	40B:C	40B:C	60B:C	60B:C	120B:C	80B:C
Agent Type		BC	BC	BC	BC	BC	BC	BC	BC
Item Part Number		88-24280	88-24397	88-24295	88-24395	88-24297	88-24399	88-24292	88-24401
Valve Material		Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Shell Material		Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Shipping Weight	lb.	5.4	5.4	10.4	10.4	18.0	18.0	33.0	33.0
	kg	2.11	2.11	4.70	4.70	8.16	8.16	15.00	15.00
Operating Pressure	PSI	195	195	195	195	195	195	195	195
	Bar	13.4	13.4	13.4	13.4	13.4	13.4	13.4	13.4
Temperature Range	°F	-40 to 120	-65 to 120	-40 to 120	-65 to 120	-40 to 120	-65 to 120	-40 to 120	-65 to 120
	°C	-40 to 49	-54 to 49	-40 to 49	-54 to 49	-40 to 49	-54 to 49	-40 to 49	-54 to 49
Discharge Time	sec.	9.0	9.0	13.5	13.5	18.0	22.0	29.0	29.0
Discharge Range	ft.	10 to15	10 to15	12 to18	12 to18	16 to 20	16 to 20	16 to 20	16 to 20
	m	3.1 to 4.6	3.1 to 4.6	3.7 to 5.5	3.7 to 5.5	4.9 to 6.1	4.9 to 6.1	4.9 to 6.1	4.9 to 6.1
Unit Height	in.	14.875	14.875	15.250	15.250	19.150	19.150	21.130	21.130
	cm	37.78	37.78	38.70	38.70	48.59	48.59	53.60	53.60
Unit Width	in.	5.50	5.50	7.25	7.25	8.13	8.13	9.25	9.25
	cm	13.97	13.97	14.70	14.70	20.65	20.65	23.50	23.50
Shell Diameter	in.	3.00	3.00	4.25	4.25	5.25	5.25	7.25	7.25
	cm	7.62	7.62	10.80	10.80	13.33	13.33	18.41	18.41
UL Listed		Yes	No	Yes	No	Yes	No	Yes	No
ULC Listed		No	Yes	No	Yes	No	Yes	No	Yes
USCG Approval		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USCG Bracket		MB-250 (Included)	MB-250 (Included)	MB-5 (Optional)	MB-5 (Optional)	UB-10 (Optional)	UB-10 (Optional)	UB-20 (Optional)	UB-20 (Optional)

400 Main Street
Ashland, MA 01721
Ph: (508) 881-2000
Fax: (508) 881-8920
www.kiddefiresystems.com