

Water

Fire Extinguishers



Features

- Agency Listings:
 - UL Listed
 - ULC Listed
- Size: 2½ gallons
- Maximum performance at both high and low temperatures (when the optional AC40 antifreeze package is used)
- Full stainless steel cylinders that resist corrosion, dents and punctures
- Chrome plated brass valve and stainless steel handle
- Universal pictorial labels with operator instructions
- Five year interval between hydrotests
- Six year warranty

UL Listed Model

- KW

ULC Listed Model

- KW-C

UL and ULC Listed Models
Six Year Warranty



Number One Choice for Virtually all Class-A Type Hazards—The Kidde Fire Systems Pressurized Water Fire Extinguishers provide an ideal solution for occupancies where deep seated Class A combustibles, such as wood or paper, are present.

Perfect for storerooms, schools, offices or any normal occupancy where a minimum fire rating is required, the KW and KW-C models provide long range, fast and effective fire protection.

Specifications

		KW	KW-C	AC40 Antifreeze
Nominal Capacity		2.5 Gallons	2.5 Gallons	10 lb.
		9.46 Liters	9.46 Liters	4.54 kg
UL Fire Rating		2A	2A	N/A
Agent Type		Water	Water	Acetate
Item Part Number		88-24324	88-24435	88-00792
Valve Material		Plated Brass	Plated Brass	N/A
Shell Material		Stainless Steel	Stainless Steel	N/A
Shipping Weight	lb.	8	8	11
	kg	3.6	3.6	4.9
Operating Pressure	PSI	100	100	N/A
	Bar	6.89	6.89	N/A
Temperature Range	°F	33 to 120	33 to 120	-40 to 120
	°C	1 to 49	1 to 49	-40 to 49
Discharge Time	sec.	55	55	N/A
Discharge Range	ft.	30 to 45	30 to 45	N/A
	m	9.1 to 13.7	9.1 to 13.7	N/A
Unit Height	in.	24.75	24.75	N/A
	cm	62.87	62.87	N/A
Unit Width	in.	9.0	9.0	N/A
	cm	22.86	22.86	N/A
Shell Diameter	in.	7.0	7.0	N/A
	cm	17.78	17.78	N/A
UL Listed		Yes	No	N/A
ULC Listed		No	Yes	N/A
Retention Bracket		UB-20 (Optional)	UB-20 (Optional)	N/A

400 Main Street
Ashland, MA 01721
Ph: (508) 881-2000
Fax: (508) 881-8920
www.kiddefiresystems.com