

Wet Chemical Fire Extinguishers



Features

- Agency Listings/Approvals:
 - UL Listed
 - ULC Listed
- Available in Two Sizes: 6 Liters and 2½ gallons
- Chrome plated brass valve, stainless steel cylinder, handle, lever and pull pin
- Non-metal finger guard for safer operation and protective nozzle orifice seal to prevent nozzle blockage.
- Universal pictorial labels with operator instructions
- Five year interval between hydrotests
- Six year warranty

UL Listed Models

- KWC100
- KWC250

ULC Listed Models

- KWC100-C
- KWC250-C

**UL and ULC Listed Models
Six Year Warranty**



The Only Choice for Commercial Restaurants—The Kidde Fire Systems Wet Chemical Portable Fire Extinguishers are designed specifically to meet the challenges of today's modern cooking operations. Tested and approved to Underwriters Laboratories (UL) new test criteria, Kidde Fire Systems Wet Chemical Extinguishers offer safe, effective fire protection solutions for cooking media fires. The Kidde Fire Systems line of Wet Chemical Extinguishers meet the 1998 Edition of NFPA Pamphlet #10, *Standard for Portable Fire Extinguishers*, and are equipped with a field replaceable nozzle seal to prevent contaminants and grease laden vapors from clogging the discharge hose and nozzle orifice.

Specifications

		KWC100	KWC100-C	KWC250	KWC250-C
Nominal Capacity	G	1.59	1.59	2.50	2.50
	L	6.00	6.00	9.43	9.43
UL Fire Rating		K	N/A	K	N/A
ULC Fire Rating		N/A	K	N/A	K
Agent Type		Potassium Acetate	Potassium Acetate	Potassium Acetate	Potassium Acetate
Item Part Number		88-24327	88-24421	88-24330	88-24443
Valve Material		Plated Brass	Plated Brass	Plated Brass	Plated Brass
Shell Material		Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Shipping Weight	lb.	15	15	19	19
	kg	6.4	6.4	8.6	8.6
Operating Pressure	PSI	100	100	100	100
	Bar	6.89	6.89	6.89	6.89
Temperature Range	°F	40 to 120	40 to 120	40 to 120	40 to 120
	°C	4.4 to 49	4.4 to 49	4.4 to 49	4.4 to 49
Discharge Time	sec.	55 to 60	55 to 60	75 to 80	75 to 80
Discharge Range	ft.	8 to 12	8 to 12	8 to 12	8 to 12
	m	2.4 to 3.6	2.4 to 3.6	2.4 to 3.6	2.4 to 3.6
Unit Height	in.	19.5	19.5	24.5	24.5
	cm	49.53	49.53	62.23	62.23
Shell Diameter	in.	7	7	7	7
	cm	17.78	17.78	17.78	17.78
UL Listed		Yes	No	Yes	No
ULC Listed		No	Yes	No	Yes
Wall Hanger Included		Yes	Yes	Yes	Yes
Bi-Lingual Use Placard Included		Yes	Yes	Yes	Yes
Nozzle Tip Finger Guard		Yes	Yes	Yes	Yes
Nozzle Tip Orifice Seal		Yes	Yes	Yes	Yes

400 Main Street
Ashland, MA 01721
Ph: (508) 881-2000
Fax: (508) 881-8920
www.kiddefiresystems.com