

Wheeled Dry Chemical

Pressure Transfer Models 300 lb. and 350 lb. Fire Extinguishers



Features

- Agency Listings/Approvals:
 - UL Listed
 - USCG Approved
- 55 cu. ft. nitrogen cylinder with quick opening "T" handle
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Corrosion resistant zinc epoxy primer and red polyurethane paint finish
- Quick release 50 ft. discharge hose with brass, chrome plated ball type shut-off nozzle
- Stainless steel fill opening with brass (4 in.), chrome plated cap
- Smooth rolling 36 in. x 6 in. wheels (standard)
- Operating temperature -65°F to 120°F (-54°C to 49°C)
- Twelve year interval between hydrotests
- Six year warranty

Pressure Transfer Fire Extinguisher Models

- K300MPT
- K300RPT
- K300KPT

UL Listed
Six Year Warranty



Easy to Transport and Operate—The Kidde Fire Systems Wheeled Dry Chemical Extinguishers provide fast delivery of dry chemical directly to the hazard. The Wheeled Dry Chemical Fire Extinguishers can be used in a variety of applications, such as: oil refineries, offshore drilling rigs, ship docks, chemical plants, warehouse and aircraft ramps, remote construction sites, flammable liquid storage and loading areas and flammable gas processing and storage areas. Kidde Fire Systems Wheeled Dry Chemical Fire Extinguishers bring reliable service to the fire extinguisher industry.

Specifications

		K300MPT	K300RPT	K300KPT
Nominal Capacity	lb.	300	350	300
	kg	136	159	136
Nitrogen Cylinder	cu.ft.	55	55	55
	l	1557.43	1557.43	1557.43
UL Fire Rating		40A-320B:C	320B:C	320B:C
Agent Type		ABC	Regular	Purple K
Item Part Number		88-24454	88-24455	88-24456
Shell Material		Steel	Steel	Steel
Temperature Range	°F	-65 to 120	-65 to 120	-65 to 120
	°C	-54 to 49	-54 to 49	-54 to 49
Discharge Time	sec.	60	70	67
Discharge Range	ft.	30 to 40	30 to 40	30 to 40
	m	9.1 to 12.2	9.1 to 12.2	9.1 to 12.2
Unit Height	in.	57	57	57
	cm	145	145	145
Unit Width	in.	34	34	34
	cm	86.0	86.0	86.0
Unit Depth	in.	39	39	39
	cm	99.0	99.0	99.0
Safety Disc Burst Range	PSI	400 to 500	400 to 500	400 to 500
	Kpa	2760 to 3450	2760 to 3450	2760 to 3450
Hose Length	ft.	50	50	50
	m	15.2	15.2	15.2
Hose Diameter	in.	1	1	1
	mm	25.4	25.4	25.4
Steel Wheels	in.	36 x 6	36 x 6	36 x 6
	mm	914 x 152	914 x 152	914 x 152
UL Listed		Yes	Yes	Yes
USCG Approval		Yes	Yes	Yes

400 Main Street
Ashland, MA 01721
Ph: (508) 881-2000
Fax: (508) 881-8920
www.kiddefiresystems.com