



“Brahma” Single Waterway Monitor

Features on CM-1250B-3S & CM-1250B-4S

- Corrosion resistant brass construction
- Flows up to 1250 gpm with minimum friction loss
- Grease fittings at each swivel joint
- Full 3" (76mm) waterway
- 2-1/2" MNST outlet
- Stainless steel ball bearings at each swivel joint
- 360 degree rotation w/positive lock
- Vanes at each elbow to reduce friction loss, improving range of stream
- Optional inlet flanges 3" or 4" flange

Features on CM-2000B & CM-2000H

- Corrosion resistant brass construction
- Flows up to 2000 gpm with minimum friction loss
- Grease fittings at each swivel joint
- Full 4" (100 mm) waterway
- Stainless steel ball bearings at each swivel joint
- 360 degree rotation w/positive lock
- Vanes at each elbow to reduce friction loss, improving range of stream
- 4" inlet flange and 3-1/2" MNST outlet



Suitable

- Suitable with water or all types of foam concentrates
- Suitable for Marine, Offshore, Industrial or other corrosive environment

Accessories

- Monitor Nozzles
- Self-Educting Nozzles
- Hydrant Mount Stand

Part No:	Waterway	Inlet	Discharge	Material	Vertical Travel	Horizontal Rotation
CM-1250B-3S	3"	3" Flange	2.5" MNST	Brass	150	360
CM-1250B-4S	3"	4" Flange	2.5" MNST	Brass	150	360
CM-2000B	4"	4" Flange	3.5" MNST	Brass	150	360
CM-2000H	4"	4" Flange	3.5" MNST	Brass	150	360

CHEMGUARD
 204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com